

# IQAC

## Inter-Agency Quality Assurance Committee

Standard Form for Aggregate Base Submittal

**Type II Aggregate:** Section 704.03.04 Uniform Standard Specifications for Public Works Off-Site Construction Clark County Area, Nevada

Date of Submittal: \_\_\_\_\_

Supplier's Name: \_\_\_\_\_

General location (ie: cross streets): \_\_\_\_\_

Date sampled: \_\_\_\_\_

Legal description: \_\_\_\_\_

Section: \_\_\_\_\_ Township: \_\_\_\_\_ Range: \_\_\_\_\_

Sieve Analysis			Test Name	Test Results	Specification
Sieve Size	Percent Passing	Specifications %			
1"		100	Moisture Density Relationship	-	-
3/4"		90-100	<i>Maximum Density (pcf)</i>		-
1/2"		-	<i>Optimum Moisture %</i>		-
3/8"		-	Percent of Wear		45% Maximum
No. 4		35-65	Fractured Faces		70% Minimum
No. 8		-	Plasticity Index		Give Maximum From Table 1
No. 16		15-40	Liquid Limit		35% Maximum
No. 30		-	Resistance (R value)		78 Minimum
No. 50		-	Sp. gravity of + 3/4"		
No. 100		-	Soluble Sulfates		0.3 Maximum
No. 200		2-10	USCS Classification		
			Color		

**A graph of the Moisture Density Relationship must be attached below.**

Submitted By: \_\_\_\_\_ P.E. Stamp:  
(Signature)

\_\_\_\_\_  
(Print Name)

\_\_\_\_\_  
(Title)